

## DTEC SOLVENT PHOTO SATIN

RESIN-COATED PAPER WITH SLP

Weight DIN EN ISO 536	g/m <sup>2</sup>	226	± 7
Thickness DIN EN ISO 534	µm	213	± 7
	mil	8.4	± 0.3
Gloss BYK (60°) ISO 2813		22	± 5
Colour Elrepho UVO (D65) ISO 2469	L	93,7	± 0,6
	a	-0,3	± 0,4
	b	-1,6	± 0,6
	Delta b	11,4	± 0,6
CIE whiteness (D65/10°) min. ISO 2469		> 143	
Opacity min. ISO 2469	%	> 94	

### Printability

Simplex printable

### Laminatability

Hot & cold

### Printing Technology

- Inkjet solvent
- Inkjet latex
- Inkjet UV

### Compatibility

Excellent results on all eco, mild and hard solvent printers as well as on latex and UV printers. Profiled for HP Latex printers 310, 330, 360, 370.

### Benefits & Properties

- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- Optimum handling properties
- High light fastness
- Outdoor durability

- Outstanding lay-flat performance
- Fast dry
- PVC free

## Key Applications

### Sign & Display Graphics

- POS signage
- Exhibition graphics
- Photo prints
- Commercial posters for indoor and outdoor applications

## Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.